



Best in class robust heavy duty frame having heavy duty forged tines.

Heavy duty springs to absorb sudden impact.

Superior powder coated paint.



SECONDARY TILLAGE IMPLEMENT FOR BETTER SOIL PULVERIZATION, EFFICIENT UPROOTING OF WEEDS AND LEFT OVER CROP RESIDUE.

HEAVY DUTY RANGE



SALIENT FEATURES

- Secondary tillage implement used for aerating & loosing of soil.
- Better pulverization for smooth seed bed preparation.
- Economical & time saver for seed bed preparation.
- Best suitable for use in stoney & rooty soil conditions.
- Superior powder coated paint helps preventing rust.
- Springs provides the damping effect like if one tine is obstructed, the other continues to work at proper depth.
- Heavy duty springs with 10 mm WD for over coming obstruction like stones/hooks etc.



Heavy Duty Frame Channel for toughest operation



Best quality heavy duty springs



Forged tines for hard soil made up of EN9 material



Superior powder coated paint prevent from rust.

		TEC	CHNICAL DATA		NO.
DESCRIPTION		9 TINE	9 TINE	11 TINE	13 TINE
FRAME (mm)	AME (mm) 75x40 (Ch		100x50 (Channel)		
TINES (mm)	π	50x25 FORGED			
ENGTH (mm)		2039		2492	2945
WIDTH (mm)	141	878			
HEIGHT (mm)	Ī	1157			
3 POINT LINKAGE		F-65X16 & R - 50X16			
SPRING		10 WD /50 OD / 28.5 Coil			
WEIGHT (kg.) approx.	ΔĪĞ	270 Kg.	290 Kg.	370 Kg.	440 Kg.
TRACTOR POWER (hp) 🚜 45+			55+	65+	

*The Product & Specifications are subject to change / discontinue without any notice on the sole discretion of manufacturer.

TECHNICAL SPECIFICATION

WORLD'S NO.
HEAVY DUTY RANGE

SONALIKA INDUSTRIES

(A UNIT OF INTERNATIONAL CARS & MOTORS LTD.)

Works & Admin Office: Vill. Chak Gujran, Jalandhar Road, Hoshiarpur -146 022 (Pb.), India

Tel.: +91 99149-34522, +91 1882-501320, Email: info@sonalikaindustries.com

Authorised Dealer