

Best suitable for tillage and earthing operation

Specially designed J type boron steel blades

Heavy duty robust structure

REVERSE FORWARD

ROTARY TILLER



WORLD'S NO. 1
HEAVY DUTY RANGE

TECHNICAL SPECIFICATION



Specially design for 15-30 hp tractor.



Best for earthing up operation for sugarcane field.



J pocket type blade



Specially designed gearbox for operation rotor in dual direction

	SLRT 0.6	SLRT 0.8
Overall Length mm	790 mm	951.5 mm
Overall Width mm	 970 mm	970 mm
Overall Height mm	 950 mm	950 mm
Tilling Width mm	660 mm	820mm
Tractor Power hp	 15-30	15-30
3 point Type	CAT-I	CAT-I
No. Of Blade	 18	22
Transmission type	 Chain Drive	Chain Drive
Input RPM	 540	540
Rotor RPM @ 540	 244	244
Standard Blade	J Type	J Type
Rotor Tube Dia	Ø 73 mm	Ø 73 mm
Rotor Swing Dia	Ø 455 mm	Ø 455 mm
Max. Working Depth	 150 mm	150 mm
Weight kg	 155 Kg	170 Kg
Driveline Safety	Shear Bolt	Shear Bolt
Recommended Row to Row distance (feet)	3.5 to 4 feet	4.5 to 5 feet

*The Product & Specifications are subject to change / discontinue without any notice on the sole discretion of manufacturer.

WORLD'S NO. 1
HEAVY DUTY RANGE

SONALIKA INDUSTRIES

(A UNIT OF INTERNATIONAL CARS & MOTORS LTD.)

Works & Admin Office: Vill. Chak Gujran, Jalandhar Road, Hoshiarpur -146 022 (Pb.), India

Tel.: +91 99149-34522, +91 1882-501320, Email: info@sonalikaindustries.com

Authorised Dealer