



ULTIMATE SOWING SOLUTION

SUPER SEEDER

- Equipped with most wanted challenger HD rotavator
- Residue management, land preparation & sowing in a single go
- Ensures faster decomposition of crop residues
- Higher crop yield in comparison to traditional methods
- Italian boron special material LJF blades
- Stainless steel 14" bigger disc assy.



HEAVY DUTY RANGE



Sonalika Super Seeder allows combined application of soil preparation, and sowing with fertilizer. It mixes the stubble, thus enhancing the organic value of the soil. Direct sowing of seeds helps in reducing cost & saving time.

SALIENT FEATURES

- Zero burning solution for paddy straw management.
- Solution for land preparation to sowing in a single pass.
- Wheat sowing & fertilizer application at the same time.
- Rear kit provided for converting super seeder to rotary tiller.
- Low maintenance ensuring.
- Higher fuel efficiency.
- Inclined disc type furrow openers for seed sowing.
- Heavy duty multispeed gear box.
- Safety covers on all the moving parts



Stainless steel disc



Heavy duty multispeed gear box



Separate chamber for seed & fertilizer



LJF boron steel blade



Heavy duty top mast



Dust proof chain cover

TECHNICAL DATA				
Size in feet		6	7	8
Model		SSLSS-10	SLSS-11	SLSS-14
Working width (mm)	l₩I	1744	2050	2285
No. of blades		42	48	54
No. of flanges	Ø	8	9	11
Tractor Power (hp)	4 0	50	55 & above	
Gear box		Multi speed (13:23)		
Side drive		Gear drive		
Seed & fertilizer mechanism		Aluminium fluted roller type		
No. of inverted disc type tyne		10 sets	11 sets	13 sets
Weight (kg. approx.)	516	895	880	1010

SONALIKA CLIDER CEEDER

*The Product & Specifications are subject to change / discontinue without any notice on the sole discretion of manufacturer

WORLD'S NO.
HEAVY DUTY RANGE

SONALIKA INDUSTRIES

(A UNIT OF INTERNATIONAL CARS & MOTORS LTD.)

Works & Admin Office: Vill. Chak Gujran, Jalandhar Road, Hoshiarpur -146 022 (Pb.), India Tel.: +91 9914934522, +91 1882-501320, Email: info@sonalikaindustries.com

Authorised Dealer

039093A